# MAXIMUM STREWGTH TOUR SET PLUS EPOXY W/BEADS PART A+B

### SAFETY DATA SHEET

VB 1002-50B

# SECTION 1 - PRODUCT IDENTIFICATION

PRODUCT NAME:

EP 745 PART A

PRODUCT CODE:

745-A

PRODUCT CLASS:

Ероху

CAS NUMBER:

CAS NO.

**COMPANY NAME:** 

INNOVATIVE RESIN SYSTEMS, INC.

COMPONENT

**257 WILSON AVENUE** NEWARK, NJ 07105

Bisphenol A epoxy resin Carbon Black

25068-38-6 1333-86-4

973-465-6887

**EMERGENCY ASSISTANCE: CHEMTEL** 

US, Canada: 1-800-255-3924

Mexico: 01-800-099-0731, China: 400-120-0751

All Others: 1-813-248-0585

### SECTION II - HAZARDS IDENTIFICATION

# Information In accordance with 29 CFR 1910.1200

### **GHS Classification:**

Skin Irritation Category 2 Eye Irritation Category 2A Skin Sensitization Category 1

#### **GHS Label elements:**

**Pictograms** 

Signal Word: Warning

### **Hazard Statements:**

H315 Causes skin irritation

H317 May cause an allergic skin reaction

Causes serious eye irritation H319

# **Precautionary Statements:**

Avoid breathing dust/fume/gas/mist/vapours/spray. P261

Wash thoroughly after handling P264

Wear protective gloves/protective clothing/eye protection/face protection. P280

IF ON SKIN: P303

Wash with plenty of soap and water. P352

P333 If skin irritation or rash occurs:

Get medical advice/attention. P313

Take off contaminated clothing and wash before reuse. P362

P304

Remove victim to fresh air and keep at rest in a position comfortable for

P340 breathing.

IF IN EYES: P305

Rinse cautiously with water for several minutes. P351

Product Code: EP 745-A Approved Date 6/17/24

P338 Remove contact lenses, if present and easy to do. Continue rinsing.

Dispose of contents/container according to Federal state/Provincial and local

P501 governmental regulations.

### **OTHER HEALTH HAZARDS:**

Lung sensitization (e.g. Allergy, asthma) may be evidenced by wheezing with shortness of breath and cough.

# SECTION III - COMPOSITION / INFORMATION ON INGREDIENTS

COMPONENT	CAS NO.	<u>%</u>	
Bisphenol A epoxy resin	25068-38-6	90-99	
Carbon Black	1333-86-4	<1	

# SECTION IV - FIRST AID MEASURES

#### SKIN CONTACT:

Immediately remove contaminated clothing or shoes, wipe excess from skin and flush with plenty of water for at least 15 minutes. Use soap if available or follow by washing with soap and water. Do not reuse clothing until thoroughly cleaned.

#### **EYE CONTACT:**

Immediately flush eyes with plenty of water for at least 15 minutes while holding eyelids open and seek medical attention.

### **INHALATION:**

Remove victim to fresh air and provide oxygen if breathing is difficult. Give artificial respiration if not breathing and seek medical help immediately.

# **INGESTION:**

Do not give any liquids (do not induce vomiting) if victim is unconscious or very drowsy. Get medical help immediately.

#### SECTION V - FIRE FIGHTING MEASURES

### **EXTINGUISHING MEDIA:**

Use Dry Chemical, Carbon Dioxide, Foam or Water Fog

# SPECIAL FIRE FIGHTING PROCEDURES AND PRECAUTIONS:

Full emergency equipment with self-contained breathing apparatus and full protective clothing should be worn by fire fighters. Do not enter a confined space without full bunker gear, including a positive pressure NIOSH approved self-contained breathing apparatus. During fire, irritating and toxic gases may be generated by thermal decomposition or combustion.

# SECTION VI - ACCIDENTAL RELEASE MEASURES

SPILL OR LEAK PROCEDURES: Remove all sources of ignition and ventilate the area. Dike and contain spilled material and control further spillage if feasible. Cover spill with clay, sand, saw dust, vermiculite, Fuller's earth or other suitable absorbent. Collect material in non-leaking containers and seal tightly for disposal. Refer to section 13 for disposal information.

#### SECTION VII - HANDLING AND STORAGE

Handle in accordance with good industrial hygiene and safety practices. These practices include avoiding unnecessary exposure and removal of the material from eyes, skin and clothing. Employee education and training in the safe use and handling of this material are required under the OSHA Hazard communication standard. Use with adequate ventilation.

# STORAGE:

Store indoors in a cool dry place away from heat, sparks and flame. Keep containers tightly closed when not in use.

# SECTION VIII - EXPOSURE CONTROLS / PERSONAL PROTECTION

### **EYE PROTECTION:**

Safety glasses, splash goggles or face shield. Contact lenses should not be worn.

### SKIN PROTECTION:

Avoid contact with skin and clothing. Use chemical resistant protective gloves.

# RESPIRATORY PROTECTION:

Avoid breathing vapors which may be produced under some conditions such as heating or applications. Avoid breathing aerosols and mists. Use NIOSH / MSHA approved respiratory protection equipment when airborne exposure is excessive. Observe OSHA regulations for respirator use (29 CFR 1910.134).

# **VENTILATION:**

Hazard control from vapor or spray mist is ideally performed by the use of engineering controls. General or local ventilation or isolation may prove adequate to keep airborne exposures below exposure limits.

# SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL FORM:

COLOR:

**BOILING POINT:** 

WEIGHT PER GALLON: **VAPOR DENSITY:** 

**EVAPORATION RATE:** (N-Butyl Acetate)

**FLASH POINT:** FLAMMABILITY LIMITS: Liquid Black

Not available 9.4 pounds Heavier than air

Not available >300°F (PMCC)

**UEL % Not established** 

LEL % Not established Not established

**AUTO IGNITION TEMP.:** 

Note: These physical data are typical values based on material tested but may vary from sample to sample. Typical values should not be construed as a guarantee analysis of any specific lot or as specifications for the product.

# SECTION X - STABILITY AND REACTIVITY

### STABILITY:

Product is stable under normal conditions of storage and handling.

# **MATERIALS TO AVOID:**

Lewis or mineral acids, Organic bases such as primary and secondary aliphatic amines, oxidizing agents, curing agents - Considerable heat may be generated.

# **HAZARDOUS POLYMERIZATION:**

Will not occur under normal storage conditions. However, polymerization may occur over 500 Deg. F.

### **DECOMPOSITION PRODUCTS:**

By heat and fire: Carbon dioxide, carbon monoxide, Aldehydes, acids and other organic substances may be formed.

#### SECTION XI - TOXICOLOGICAL INFORMATION

### **CHRONIC STUDIES:**

Recent 2 year Bioassays in mice exposed by the dermal route to the Diglycidyl ether of Bisphenol A have yielded very limited evidence of weak carcinogenicity. The renal tumor evidence "was of no biological significance" and that the resin "is not a systemic carcinogen when applied to the dorsal skin of CF1 mice". Based on this, The international Agency for Research on cancer (IARC) concluded that DGEBPA was not classifiable as a carcinogen (IARC group 3) based on following: Human and Animal evidence - Inadequate.

DGEBPA have proved to be inactive when tested by in vivo mutagenicity assays. They have shown activity in vitro microbial mutagenicity screening tests and have produced chromosomal aberrations in cultured rat liver cells. The significance of this information to man is unknown.

#### SECTION XII - ECOLOGICAL INFORMATION

Data not available.

# SECTION XIII - DISPOSAL CONSIDERATIONS

Waste must be disposed of in accordance with federal, state and local environmental control regulations. Incineration is the preferred method. Empty containers must be handled with care due to product residue. Do not heat or cut empty containers with electric or gas torch.

### SECTION XIV - TRANSPORTATION INFORMATION

U.S. DEPARTMENT OF TRANSPORTATION GROUND: NOT REGULATED.

INTERNATIONAL MARITIME DANGEROUS GOODS CODE (IMDG):

PROPER SHIPPING NAME: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID N.O.S. (Epoxy resin)

**HAZARD CLASS OR DIVISION: 9** 

**IDENTIFICATION NUMBER: UN 3082** 

PACKING GROUP:

PG III

INTERNATIONAL AIR TRANSPORTATION (ICAO/IATA)

PROPER SHIPPING NAME: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID N.O.S. (Epoxy resin)

**HAZARD CLASS OR DIVISION: 9** 

**IDENTIFICATION NUMBER:** UN 3082

**PACKING GROUP:** 

PG III

# SECTION XV - REGULATORY INFORMATION

**TSCA STATUS:** 

All ingredients in this products are listed in the T.S.C.A. inventory.

# **CERCLA REPORTABLE QUANTITY:**

None

### **SARA TITLE III:**

SECTION 302 EXTREMELY HAZARDOUS SUBSTANCE :

None
SECTION 311/312 HAZARD CATEGORIES:
Immediate (Acute) health hazard
SECTION 313 TOXIC CHEMICALS:
None

INC

# RCRA:

If discarded in its purchased form, this product would not be a hazardous waste by listing. However, under RCRA, it is the responsibility of the product user to determine at the time of disposal, whether a material containing the product or derived from the product should be classified as a hazardous waste. ( 40 CFR 261.20-24).

# **CALIFORNIA PROPOSITION 65:**

This product contains no listed substances known to the State of California to cause cancer, birth defects or other reproductive harm, at levels which would require a warning under the statute.

SECTION XVI - OTHER INFORMATION					
HMIS RATINGS:	Health 2	Flammability 1	Reactivity 0		

**REASON FOR ISSUE:** 

Review.

# SAFETY DATA SHEET

# SECTION I - PRODUCT IDENTIFICATION

PRODUCT NAME:

EP 772 Part B

PRODUCT CODE:

772-8

PRODUCT CLASS:

Amine

CAS NUMBER:

COMPANY NAME:

INNOVATIVE RESIN SYSTEMS, INFO

COMPONENT

CAS NO.

**257 WILSON AVENUE** 

Fatty acids C-18, with tall oil fatty acids and

NEWARK, NJ 07105

triethylenetetramine

68082-29-1

973-465-6887

Triethylenetetramine

112-24-3

**EMERGENCY ASSISTANCE: CHEMTEL** 

US, Canada: 1-800-255-3924

Mexico: 01-800-099-0731, China: 400-120-0751

All Others: 1-813-248-0585

# SECTION II - HAZARDS IDENTIFICATION

# In accordance with 29 CFR 1910.1200

# **GHS Classification:**

Skin corrosion Category 1B Skin sensitization, Category 1 Serious eye damage/eye irritation Category 1

### **GHS Label Elements Pictograms**





Signal Word: Danger

# Hazard Statements:

Causes severe skin burns and eye damage H314

May cause an allergic skin reaction H317

# Precautionary statements:

Avoid breathing dust/fume/gas/mist/vapours/spray. P261

Wash...thoroughly after handling P264

Contaminated work clothing should not be allowed out of the workplace. P272 Wear protective gloves/protective clothing/eye protection/face protection. P280

P301 IF SWALLOWED:

Call a POISON CENTER or doctor/physician if you feel unwell. P312

Rinse mouth. P330

Do NOT induce vomiting. P331

IF ON SKIN: P303

Product Code: EP 772 PART B

Approved Date: 6/10/24

P361	Remove/Take off immediately all contaminated clothing.
P353	Rinse skin with water/shower.
P304	IF INHALED:
P340	Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305	IF IN EYES:
P351	Rinse cautiously with water for several minutes.
P338	Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER or doctor/physician.
P333	If skin irritation or rash occurs:
P313	Get medical advice/attention.
P363	Wash contaminated clothing before reuse.
P501	Dispose of contents/container according to Federal state/Provincial and local
	governmental regulations.

# SECTION III - COMPOSITION / INFORMATION ON INGREDIENTS

COMPONENT Fatty acids C-18, with tall oil fatty acids and triethylenetetramine	<u>CAS NO</u> . 68082-29-1	% 90-98	
Triethylenetetramine	112-24-3	3-7	

# SECTION IV - FIRST AID MEASURES

SKIN CONTACT:

Immediately remove contaminated clothing or shoes, wipe excess from skin and flush with plenty of water for at least 15 minutes. Use soap if available or follow by washing with soap

and water. Do not reuse clothing until thoroughly cleaned.

**EYE CONTACT:** 

Immediately flush eyes with plenty of water for at least 15 minutes while holding eyelids open

and seek medical attention.

**INHALATION:** respiration

Remove victim to fresh air and provide oxygen if breathing is difficult. Give artificial

if not breathing and seek medical help immediately. Turn victims head to the side.

**INGESTION:** 

In the event of ingestion, administer 1 glass of water. Do not induce vomiting and get

medical help immediately.

#### SECTION V - FIRE FIGHTING MEASURES

**EXTINGUISHING MEDIA:** 

In case of large fire use: Water Spray, Alcohol Foam. In case of small fires, use Carbon dioxide, Dry Chemical, dry sand or limestone.

SPECIAL FIRE FIGHTING PROCEDURES AND PRECAUTIONS: Full emergency equipment with self-contained breathing apparatus and full protective clothing should be worn by fire fighters. Do not enter a confined space without full bunker gear, including a positive pressure NIOSH approved self-contained breathing apparatus. During fire, irritating and toxic gases may be generated by thermal decomposition or combustion.

# SECTION VI - ACCIDENTAL RELEASE MEASURES

SPILL OR LEAK PROCEDURES: Remove all sources of ignition and ventilate the area. Dike and contain spilled material and control further spillage if feasible. Cover spill with clay, sand,

dust, vermiculite, Fuller's earth or other suitable absorbent. Collect material in non-leaking containers and seal tightly Refer to section 13 for disposal information. for disposal.

Product Code: EP 772 PART B Approved Date: 6/10/24

# SECTION VII - HANDLING AND STORAGE

Handle in accordance with good industrial hygiene and safety practices. These practices include avoiding unnecessary exposure and removal of the material from eyes, skin and clothing. Employee education and training in the safe use and handling of this material are required under the OSHA Hazard communication standard. Use with adequate ventilation.

Store indoors in a cool dry place away from heat, sparks and flame. Keep containers tightly closed when STORAGE:

not in use. Keep away from acids and oxidizers. Do not store in an iron or other reactive metal

containers.

# SECTION VIII - EXPOSURE CONTROLS / PERSONAL PROTECTION

**EYE PROTECTION:** 

Safety glasses, splash goggles or face shield. Contact lenses should not be worn.

SKIN PROTECTION:

Avoid contact with skin and clothing. Use chemical resistant protective gloves such as

neoprene

rubber gloves, nitrile rubbers gloves, cuffed butyl rubber gloves and other impermeable gloves.

RESPIRATORY PROTECTION: Avoid breathing vapors which may be produced under some conditions such as heating or applications. Avoid breathing aerosols and mists. Use NIOSH /

MSHA approved respiratory protection equipment when airborne exposure is excessive. Observe OSHA regulations for respirator use (29 CFR 1910.134).

VENTILATION: Hazard control from vapor or spray mist is ideally performed by the use of engineering controls.

General or local ventilation or isolation may prove adequate to keep airborne exposures below

exposure limits.

Liquid light Amber

149°C >1 (air = 1)

1.08

Missible

# SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL FORM:

**COLOR:** 

BOILING POINT:

VAPOR DENSITY: SPECIFIC GRAVITY:

VAPOR PRESSURE:

SOLUBILITY:

(In water)

**EVAPORATION RATE:** 

(n Butyl Acetate = 1) FLASH POINT:

FLAMMABILITY LIMITS:

Not available

Not available

>300°F (PMCC) UEL % Not established

LEL % Not established

**AUTO IGNITION TEMP.:** 

Not Known

Note: These physical data are typical values based on material tested but may vary from sample to sample. Typical values should not be construed as a guarantee analysis of any specific lot or as specifications for the product.

#### SECTION X - STABILITY AND REACTIVITY

STABILITY:

Product is stable under normal conditions of storage and handling.

MATERIALS TO AVOID:

Lewis or mineral acids, Organic bases such as primary and secondary aliphatic amines, Ketones, Aldehydes, oxidizing agents. A reaction accompanied by large heat release

occur when the product is mixed with acids.

HAZARDOUS POLYMERIZATION: Will not occur.

DECOMPOSITION PRODUCTS: By heat and fire: Carbon dioxide, carbon monoxide. Ammonia when heated. Nitrogen oxide in the fire. Nitrogen oxide can react with water vapors to form corrosive nitric acid

Product Code: EP 772 PART B

Approved Date: 6/10/24

# SECTION XI - TOXICOLOGICAL INFORMATION

Acute Oral Toxicity (LD50, Rat):

>4290 mg/kg (estimates) >2500 mg/kg (estimates)

Acute dermal Toxicity (LC50, Rat):

**Chronic Data:** 

No delayed, subchronic or chronic test data are known

# SECTION XII - ECOLOGICAL INFORMATION

Data not available.

# SECTION XIII - DISPOSAL CONSIDERATIONS

Waste must be disposed of in accordance with federal, state and local environmental control regulations. Incineration is the preferred method. Empty containers must be handled with care due to product residue. Do not heat or cut empty containers with electric or gas torch.

# SECTION XIV - TRANSPORTATION INFORMATION

PROPER SHIPPING NAME:

Amines, Liquid Corrosive, N.O.S.

**HAZARD CLASS or DIVISION:** 

8 Corrosive

UN / NA Number:

UN 2735 PG III

**PACKING GROUP:** DOT PRODUCT RQ, Lb.

None

HAZARD LABEL(S):

8 Corrosive

HAZARD PLACARD(S):

Corrosive

# SECTION XV - REGULATORY INFORMATION

TSCA STATUS:

All ingredients in this products are listed in the T.S.C.A. inventory.

CERCLA REPORTABLE QUANTITY:

None

SARA TITLE III:

SECTION 302 EXTREMELY HAZARDOUS SUBSTANCE:

None

SECTION 311/312 HAZARD CATEGORIES:

None

**SECTION 313 TOXIC CHEMICALS:** 

None

# RCRA:

It is the responsibility of the product user to determine at the time of disposal, whether a material containing the product or derived from the product should be classified as a hazardous waste. (40 CFR 261.20-24).

# **CALIFORNIA PROPOSITION 65:**

This product contains no listed substances known to the State of California to cause cancer, birth defects or other reproductive harm, at levels which would require a warning under the statute

# SECTION XVI - OTHER INFORMATION

Product Code: EP 772 PART B

Approved Date: 6/10/24

HMIS RATINGS: Health 3 Flammability 1 Reactivity 0

Product Code: EP 772 PART B Approved Date: 6/10/24